

## DESCRIPTION

- Suitable for car and light trucks up to 4 ton
  - Symmetric - large swing arm area designed to cater for various lifting positions
  - Secure - rubber doors guard prevent damages when moving in/out of the vehicle.
- Heavy duty arm restraints and hydraulic hose guards designed to be safe and long lasting
- Smooth lift operation - nylon glide blocks are used to provide durable and smooth operation
  - Arm pads - adjustable screw with stackable rubber lifting pad

## SPECIFICATIONS TABLE

SPECIFICATIONS	
Capacity	4.0 ton
Overall Width	3402 mm
Width between Columns	2752 mm
Drive-thru Width	2437 mm
Overall Height	3705 mm
Under Bar Clearance	3593 mm
Height to Lowered Lift Pad	114 mm
Height to Raised Low Lift Pad	159 mm
Arm Type	2-stage
Arm Design	Symmetric
Front Arm	802 - 1202 mm
Rear Arm	802 - 1202 mm
Maximum Lifting Height	1756 mm
Lift Time / Lower Time	50 / 40 sec
Safety Valve	Yes
Mechanical Safety Latches	Yes
Type of Equalization	Cable
Hydraulic System	Chain over
Hydraulic Cylinder with Double Seal	Yes
Overhead Limit Switch	Yes
Mechanical Safety Lock	2 sides manual
Double Telescopic Pad Screw	Optional
Door Guard	Yes
Power Supply	380V, 3 Ph, 50Hz 220V, 1 Ph, 50-60Hz