

DESCRIPTION

- Designed for car and light trucks up to 4 ton
 - Semi-symmetric - large swing arm area designed to cater for various lifting position
 - Secure - rubber doors guard prevent damages when moving in/out of the vehicle.
- Heavy duty arm restraints and hydraulic hose guards designed to be safe and long lasting
- Smooth lift operation - nylon glide blocks are used to provide durable and smooth operation
 - Arm pads - adjustable screw with stackable rubber lifting pad

SPECIFICATIONS TABLE

<u>Technical Data</u>		<u>Technical Data</u>	
Drive	Electrical Hydraulic	Rear Slip Plate Length	1517 mm
Maximum Capacity	3.5T	Primary Lift Height	1860 mm
Overall Length	4300 mm	Secondary Lift Height	456 mm
Primary Runway Length	4000 mm	Runway Initial Height	330 mm
Secondary Runway Length	1400 mm	Primary Lifting Time	40 - 60 s
Overall Width	2160 mm	Primary Lowering Time	40 - 60 s
Primary Platform Width	620 mm	Secondary Lifting Time	10 - 30 s
Secondary Platform Width	550 mm	Secondary Lowering Time	10 - 30 s
Width between Runways	920 mm	Working Temperature	5 - 40°C
Min. Wheel Base-4 Wheel Alignment	1915 mm	Air Supply Requirements	8 - 10 bar
Max. Wheel Base-4 Wheel Alignment	3280 mm	Power Supply	380V, 3Ph, 50Hz or 220V, 1Ph, 50-60Hz