

DESCRIPTION

- Pressure limiter, air filter and oil reservoir for lubricant to ensure the safe operation and durability of the machine
- Mount / demount tools with plastic protection prevent any damages on the alloy rim during operation
- The special design of the tilt-back post guarantees minimum tension even when hard tyres are mounted or demounted
- High ground clearance of foot pedals facilitate operations during mounting and demounting
- Tried, tested and proven clamps with covered sliding grooves ensure operator's safety

SPECIFICATIONS TABLE

SPECIFICATIONS	Tilt-back
Tire Lever	●
Manual Inflator	●
Plastic Protector for Clamping Jaws	●
Holder for Tire Lubricant Container	●
Plastic Protector for Mounting Tools	●
MH	Optional
Servicing Unit with Pressure Relief Valve and Oiler	●
Maximum Wheel Diameter	39" (1000 mm)
Maximum Tire Width	13" (330 mm)
Inner Clamping Range	12" - 22"
Outer Clamping Range	10" - 20"
Turntable Speed	6.5 rpm
Bead Breaking Force	10 kN
Compressed Air Supply	8 - 12 bar
Power Supply	230V, 1 Ph, 50-60Hz 380V, 3 Ph, 50-60Hz
Weight	173 kg
Dimensions (D*W&H)	1040x892x1770 mm