

# Ideal for applications where compressed air is not available

Digital B-RAD is the world's first digital, cordless, and lithium-ion battery tool on the market. With advanced patented technology containing digital display and single increment torque settings.

BATTERY



## FEATURES


- Available with torque and angle option
- Programmable pre-set torque settings
- Latest lithium-ion 18V battery technology
- High accuracy of +/-5%
- Automatic 2-speed gearbox
- Patented product

## CASE

Durable, lightweight, shock proof. Designed to protect your RAD investment.



| PART NUMBER | DESCRIPTION         |
|-------------|---------------------|
| 26400       | DB-RAD ANGLE OPTION |



## IMPERIAL

| PART NUMBER | TOOL MODEL    | DRIVE SIZE | TORQUE (ft. lbs.)<br>LOW HIGH | RPM | WEIGHT (lbs.) | NOISE LEVEL | DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D |
|-------------|---------------|------------|-------------------------------|-----|---------------|-------------|-------------|-------------|-------------|-------------|
| 21779       | DB-RAD 500-2  | 0.75"      | 50 500                        | 59  | 11            | 80 db       | 12.67"      | 2.5"        | 2.5"        | 10.25"      |
| 21783       | DB-RAD 1000-2 | 0.75"      | 100 1000                      | 19  | 11.6          | 80 db       | 13"         | 2.5"        | 2.5"        | 10.25"      |
| 21787       | DB-RAD 1500-2 | 1.0"       | 150 1500                      | 17  | 11.8          | 80 db       | 13"         | 2.7"        | 2.7"        | 10.50"      |
| 24965       | DB-RAD 3000-2 | 1.0"       | 300 3000                      | 13  | 19.5          | 80 db       | 15.2"       | 3.2"        | 3.2"        | 10.5"       |

## METRIC

| PART NUMBER | TOOL MODEL      | DRIVE SIZE | TORQUE (Nm)<br>LOW HIGH | RPM | WEIGHT (Kg) | NOISE LEVEL | DIMENSION A (mm) | DIMENSION B (mm) | DIMENSION C (mm) | DIMENSION D (mm) |
|-------------|-----------------|------------|-------------------------|-----|-------------|-------------|------------------|------------------|------------------|------------------|
| 22876       | DB-RAD 700-2-M  | 0.75"      | 70 700                  | 59  | 5.0         | 80 db       | 321              | 63               | 63               | 279              |
| 22878       | DB-RAD 1400-2-M | 0.75"      | 140 1400                | 19  | 5.2         | 80 db       | 330              | 63               | 63               | 279              |
| 22880       | DB-RAD 2000-2-M | 1.0"       | 200 2000                | 17  | 5.3         | 80 db       | 330              | 68               | 68               | 279              |
| 24966       | DB-RAD 4000-2-M | 1.0"       | 400 4000                | 9   | 7.1         | 80 db       | 398              | 81               | 81               | 279              |

Accuracy of +/-5%, Repeatability of +/-2%